



TONEWOOD™ PERFORATED

KEY FEATURES

- Wood Veneer, Laminates and Custom Finish Facings
- FSC Certified Materials Available
- Optional Black Acoustical Fleece Backing
- Wood Veneer Face is Perforated from a Range of Design Styles & Pattern Options
- Perforation Size, Configuration & Selection of Straight or Compound
- Additional Absorption of Low Frequency Sound Energy May be Obtained with Simple, Alternate Mounting Methods
- Custom-Printed Digital Imaging Available
- Easy to Install with Fully-Concealed Mounting Hardware Included
- Up to 10 LEED Credits May Apply With Installation of These Products

Schools EQ Prerequisite 3 & Credit 9, MR 4.1 & 4.2, MR 5.1 & 5.2, IEQ 4.1 & 4.2 • Innovation in Design (ID)

WARRANTY

AVL Systems' *Limited Warranty* extends for ONE FULL YEAR from original date of shipment.

* Sound absorption tests performed using premium glass fiber back-panel under specific conditions that will not be the same for all applications. Actual installation conditions may yield different results.

* Standard materials have dimensional and weight variations. Calculations are approximate and represent material averages to the best of our knowledge.

©Copyright 2019, AVL Systems, Inc. - The use or reproduction of any trademarks/information/terminology listed on this document is prohibited without the expressed written consent of AVL Systems, Inc. AVL Systems' literature, presentations and published data are correct to the best of our knowledge at time of publication. AVL Systems, Inc. reserves the right to change or amend any of the products or the information presented or published without liability or notice.

TECHNICAL FEATURES

- **Core:** Fire Rated FRP or Fire Rated MDF
- **Thickness:** ¾"
- **Panel Sizes:** Any Size Up to 48" x 120"
- **Standard Plank Size:** 5" x 96"
- **Special Sizes & Shapes:** Available Upon Request
- **Edge Profile:** Flush or Reveal, Plain or Wood Finish
- **Facing:** Wood Veneer, Laminates and Custom Finish Facings
- **Finish:** Natural, Stain, Lacquer, Paint, Custom
- **Fasteners:** Z-Clip, Z-Bar, Ceiling Lay-In
- **FSC Certifications:** FSC Mix, FSC 100%
- **Sound Absorption:** Optional AcousTech™ or TheaterBlack™ Backing
- **Fire Performance:** Class 1/A, UL 723 / ASTM E84

ACOUSTICAL DATA

Acoustical Performance - Absorption Coefficients							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
Type A Mounting (+ 2" TheaterBlack™ Glass Fiber Backing)							
ToneWood™ Perforated Natural	0.03	0.03	0.01	0.02	0.01	0.01	0.00
ToneWood™ Perforated 22	0.37	0.91	0.98	0.99	0.98	0.84	0.95
Type E400 Mounting (+ 2" TheaterBlack™ Glass Fiber Backing)							
ToneWood™ Perforated Natural	0.04	0.03	0.02	0.01	0.01	0.01	0.00
ToneWood™ Perforated 22	0.42	0.98	1.04	0.99	1.02	0.76	1.00

STANDARD WOOD VENEER OFFERINGS


(Other Wood Species and Slicing Options Available)




Maple PS




White Oak PS




Cherry PS



Walnut PS




Red Oak PS




Mahogany PS




Maple QD



White Oak Rift




Cherry QD



Walnut QD



Natural Birch PS



White Birch PS

